




Componi75 uno parete


For illuminating small and medium-sized spaces with white or coloured, ambient and accent lighting; can be assembled by hand, without any tools. Lighting bodies rotates through 360°.



LUMINAIRE (structure)

materials	brass, steel, aluminium
environment	interiors
mounting location	wall
emission	direct/indirect/diffused/accent/mixed light
weight	0,5 kg
tension	230V
insulation class	2
IP classification	IP20
marks	CE   
design	Luta Bettonica, Luca Melocchi, Mario Melocchi, 2009

LIGHT SOURCE

source	halogen energy saver 
socket	G9
ILCOS code	HSGST/C//UB
bulb included	yes
number of bulbs	1
power	60W (max 75W)
life	2.000 h
energy label	C
luminous flux	980 lm
colour temperature	2.900 °K

FINISHES



chrome
cod 601



satin nickel-plated
cod 602

COMPONENTS

Componi75 anello



retinato
cod 609



opalescente
quadrettato
cod 610



sfere bianco
cod 616



sfere nero
cod 615



sfere rosso
cod 617



sfere giallo
cod 618

Componi75 disco



trasparente
cod 682



satinato
cod 683



retinato
cod 684



opalescente
quadrettato
cod 685



rosso
dicroico
cod 686



giallo
dicroico
cod 687



blu
dicroico
cod 688



lente 80°
trasparente
cod 680