MELT PENDANT MINI LED









OFF

Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass elect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reœectsand enhances its environment.

2014 Year of Design **Product Weight** 1.08kg **Finishing Process** Semi-Metallised, Plated Surface Mount Shape/Diameter Dome, 11.5cm **Power Method** Mains Cable Spec H03VV-F 2 x 0,75 mm2 Cable Type/Length Clear, 250cm 6W LED **Light Source** Max Wattage 9W Lumens 800 CRI >90 **Colour Temperature** 3000K Dimmability Mains Dimmable, Leading & Trailing Edge 220-240V Voltage Environment Indoor LEDRING01Y, LEDDRIVER01EU Spares Certification/Electrical Class Certiÿed for NZ/AUS





SILVER

Code	MES04CH-PEUM2
Shade Code	MES02CH
Shade Material	Polycarbonate
Shade Colour/Finish	Silver, Mirrored
Fitting Code	LEDP07CHEU
Fitting Material	Steel
Fitting Colour/Finish	Silver, Polished
Service Offer	Quick Ship

Service Offer

GOLD

Code		MES04GO-PEUM2
Shade Cod	le	MES02G
Shade Mat	terial	Polycarbonate
Shade Cole	our/Finish	Gold, Mirrored
Fitting Co	de	LEDP07GOEU
Fitting Ma	terial	Steel
Fitting Co	lour/Finish	Gold, Polished
Service Of	fer	Quick Ship

MELT PENDANT MINI LED







ON

Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass elect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reœectsand enhances its environment.

2014 Year of Design 1.08kg **Product Weight Finishing Process** Semi-Metallised, Plated Surface Mount Shape/Diameter Dome, 11.5cm **Power Method** Mains Cable Spec H03VV-F 2 x 0,75 mm2 Cable Type/Length Clear, 250cm 6W LED **Light Source** Max Wattage 9W Lumens 800 CRI >90 **Colour Temperature** 3000K Dimmability Mains Dimmable, Leading & Trailing Edge 220-240V Voltage Environment Indoor LEDRING01Y, LEDDRIVER01EU Spares **Certification/Electrical Class** Certiÿed for NZ/AUS



COPPER

Code	MES04CO-PEUM2
Shade Code	MES02CO
Shade Material	Polycarbonate
Shade Colour/Finish	Copper, Mirrored
Fitting Code	LEDP07COEU
Fitting Material	Steel
Fitting Colour/Finish	Copper, Polished
Service Offer	Quick Ship

SMOKE

Code	MES04SM-PEUM2
Shade Code	MES02SM
Shade Material	Polycarbonate
Shade Colour/Finish	Smoke, Mirrored
Fitting Code	LEDP07CHEU
Fitting Material	Steel
Fitting Colour/Finish	Silver, Polished
Service Offer	Quick Ship

